Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH)



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

SikaLastic 560 Thixo

Use of the substance/preparation : Waterproofing product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : GILAR LTD

6 Hamatechet St. Qadima, 60920

ISRAEL

 Telephone no.
 : +972 9 899 4000

 Fax no.
 : +972 9 899 4004

 e-mail address of person
 : sales@gilar.co.il

responsible for this SDS
Emergency telephone number

: Rambam +972 4 8541900

2. HAZARDS IDENTIFICATION

Additional warning phrases: Safety data sheet available for professional user on request.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Acrylic polymer Characteristics

Ingredient name	CAS number	%	EC number	Classification	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	<2.2	265-185-4	R10 Xn; R65 R66, R67 N; R51/53	[1]
See section 16 for the full text of the R- phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

Date of issue : 02.02.2016 MSDS no. : 608215 1/5

SikaLastic 560 Thixo *** 2/5

4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention if symptoms occur.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion :

products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8)

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Date of issue : **02.02.2016 MSDS no.** : 608215 **2/5**

SikaLastic 560 Thixo *** 3/5

7. HANDLING AND STORAGE

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

<u>Ingredient name</u> <u>Occupational exposure limits</u>

Naphtha (petroleum), hydrodesulfurized heavy INSHT (Spain, 2/2009). Absorbed through skin.

STEL: 580 mg/m³ 15 minute(s). STEL: 100 ppm 15 minute(s). TWA: 290 mg/m³ 8 hour(s). TWA: 50 ppm 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapour filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Hand protection

: Chemical-resistant, impervious gloves complying with an approved stan dard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.
Colour : Various.
Odour : Characteristic.

Important health, safety and environmental information

Density : ~1.29 g/cm³ [20°C (68°F)]

Date of issue : **02.02.2016 MSDS no.** : 608215 **3/5**

SikaLastic 560 Thixo *** 4/5

10. STABILITY AND REACTIVITY

Stability: The product is stable.Conditions to avoid: No specific data.Materials to avoid: No specific data.

Materials to avoid Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation: May cause irritation.

Ingestion : Can cause gastrointestinal disturbances.

Skin contactEye contactMay cause skin irritation.May cause eye irritation.

Chronic effects: No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

Environmental effects

: Avoid contact of spilt material and runoff with soil and surface waterways. Do not empty into drains; dispose of this material and its container in a safe way.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-product should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC)

: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Packaging

: Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

ADR

Not regulated.

IMDG

Not regulated.

Marine pollutant : No

<u>IATA</u>

Not regulated.

Date of issue : **02.02.2016 MSDS no.** : 608215 **4/5**

SikaLastic 560 Thixo *** 5/5

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Classification : This product is not classified according to EU legislation.Additional warning phrases : Safety data sheet available for professional user on request.

VOC content (EU) : VOC (w/w): 4.38%

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R10-Flammable.

R65- Harmful: may cause lung damage if swallowed.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: Xn - Harmful

N - Dangerous for the environment

History

3

3

Date of printing : 15.02.2011.

Date of issue : ***.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 02.02.2016 MSDS no. : 608215 5/5