according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCeram®-500 Ceralastic

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cement / Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Italia S.p.A.

Via Luigi Einaudi 6

20068 Peschiera Borromeo

Telephone +39 02 54778 111 Telefax +39 02 54778 119 E-mail address of person EHS@it.sika.com

responsible for the SDS

1.4 Emergency telephone number

CENTRO ANTIVELENI OSPEDALE NIGUARDA

+39 02 66101029

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation. Serious eve damage, Category 1 H318: Causes serious eye damage. Specific target organ toxicity - single H335: May cause respiratory irritation.

exposure, Category 3, Respiratory

system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word Danger

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Prevention: Precautionary statements

> P261 Avoid breathing dust/ fume/ gas/ mist/

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016

Version 2.0

Print Date 17.10.2017

vapours/spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

> air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if

vou feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

> with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

Disposal:

P501 Dispose of contents/container in

accordance with local regulation.

Hazardous components which must be listed on the label:

266-043-4 Cement, portland, chemicals

Additional Labelling:

EUH208

Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Cement, portland, chemicals	Skin Irrit.2; H315	>= 10 - < 20
65997-15-1	Eye Dam.1; H318	
266-043-4	STOT SE3; H335	
Cement, alumina, chemicals	Skin Irrit.2; H315	>= 5 - < 10
65997-16-2	Eye Dam.1; H318	
266-045-5	STOT SE3; H335	
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no.	Acute Tox.3; H331	< 0,0015
247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.	Acute Tox.2; H310	

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic



Revision Date 27.01.2016 Version 2.0 Print Date 17.10.2017

220-239-6] (3:1) 55965-84-9	Acute Tox.3; H301 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410		
Substances with a workplace exposure limit :			
Quartz (SiO2)		>= 25 - < 50	
14808-60-7			
238-878-4			
calcium sulfate		>= 1 - < 2,5	
7778-18-9			
231-900-3			
01-2119444918-26-XXXX			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Excessive lachrymation

Erythema Dermatitis

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic



Revision Date 27.01.2016 Version 2.0

See Section 11 for more detailed information on health effects

and symptoms.

: irritant effects Risks

Causes skin irritation.

Causes serious eve damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

: Use extinguishing measures that are appropriate to local Suitable extinguishing media

circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion

products

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

: Try to prevent the material from entering drains or water **Environmental precautions**

courses.

6.3 Methods and materials for containment and cleaning up

: Pick up and arrange disposal without creating dust. Methods for cleaning up

Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016 Version 2.0 Print Date 17.10.2017

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust. Avoid exceeding the given

occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures

when handling chemical products

Advice on protection against

fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Store in original container. Keep in a well-ventilated place.

Observe label precautions. Store in accordance with local

regulations.

Other data : Keep in a dry place. No decomposition if stored and applied

as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
Quartz (SiO2)	14808-60-7	TWA	0,025 mg/m3	ACGIH
Cement, portland, chemicals	65997-15-1	TWA	1 mg/m3	ACGIH
calcium sulfate	7778-18-9	TWA	10 mg/m3	ACGIH

8.2 Exposure controls

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016 Version 2.0 Print Date 17.10.2017

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eve wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow

manufacturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be

used.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : powder

Colour : grey

Odour : characteristic

Odour Threshold : No data available

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Flash point : No data available

Autoignition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Oxidizing properties : No data available

pH : Not applicable

Melting point/range /

Boiling point/boiling range

Freezing point

nt _

Vapour pressure : No data available

Density : ca.1,1 g/cm3

at 20 °C

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

No data available

No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016 Version 2.0 Print Date 17.10.2017

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition

products No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016 Version 2.0



Components:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

M-Factor : 10

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic

Revision Date 27.01.2016 Version 2.0 Print Date 17.10.2017

ADR

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

 $\ensuremath{\mathsf{REACH}}$ - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: None of the components are listed (=> 0.1 %).

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/orexcluded from the regulation, and/or

exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

Other regulations : Legislative Decree February 3, 1997, 52 (Implementation of

Directive 92/32/EEC concerning the classification, packaging and labeling of dangerous substances.) and subsequent

amendments

Legislative Decree March 14, 2003, 65 (Implementation of Directives 1999/45/EC and 2001/60/EC relating to the classification, packaging and labeling of dangerous

preparation) and subsequent amendments

Legislative Decree April 9,2008, 81 (Implementation of Article

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic



Revision Date 27.01.2016

Version 2.0

1 of the Law of 3 August 2007, n. 123, concerning the protection of health and safety in the workplace.) and

subsequent amendments

Legislative Decree April 3, 2006, n.152, (Environmental

standards) and subsequent amendments

Legislative Decree February 6, 2009, 21 (Regulations for the execution of the provisions laid down in Regulation (EC) no.

648/2004 on detergents)

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation

H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.

Aquatic Acute
Aquatic Chronic
Eye Dam.

Skin Corr.

Skin Irrit.

Skin Sens.

Acute toxicity
Acute aquatic toxicity
Chronic aquatic toxicity
Serious eye damage
Skin corrosion
Skin irritation
Skin sensitisation

STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level

EC50 Half maximal effective concentration
GHS Globally Harmonized System

GHS Globally Harmonized System
IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

according to Regulation (EC) No. 1907/2006

SikaCeram®-500 Ceralastic



Revision Date 27.01.2016

Version 2.0

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic
PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!