



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

### 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Sika Rep Power**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Construction and industry.
- **Application of the substance / the mixture** Chemical product for conduction and industry.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Gilar LTD - Sika Israel  
Hamatechet st. 6, 60920 Qadima , Israel  
Phone: +972 989 94006 Mobile:+972 544 527 212 Fax: +972 989 94016
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:** +972 (0) 8994004 9

### 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Carc. 1A H350 May cause cancer.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS05, GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Cement, portland, chemicals  
Blended Portland Cement
- **Hazard statements**  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.

(Contd. on page 2)



## Safety data sheet

### According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 1)

H350 May cause cancer.

H335 May cause respiratory irritation.

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P321 Specific treatment (see on this label).  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P405 Store locked up.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

14808-60-7	Quartz (SiO <sub>2</sub> ) substance with a Community workplace exposure limit	>50%
1305-78-8	calcium oxide ☞ Eye Dam. 1, H318	5-15%
65997-15-1	Cement, portland, chemicals ☞ Eye Dam. 1, H318 ☠ Skin Irrit. 2, H315; STOT SE 3, H335	15-30%
	White OPC ☠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-15%
	Blended Portland Cement ☠ Carc. 1A, H350 ☞ Skin Corr. 1A, H314 ☠ Skin Sens. 1, H317; STOT SE 3, H335	1-5%
471-34-1	calcium carbonate	1-5%

(Contd. on page 3)



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 2)

	Neopentilglycol Eye Dam. 1, H318	<1%
	Stannous Sulfate STOT RE 2, H373 Aquatic Acute 1, H400 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<1%
65997-17-3	Fibrous Glass	1-5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

#### · 4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Wash thoroughly with soap and water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Firefighting measures

#### · 5.1 Extinguishing media

#### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · 5.2 Special hazards arising from the substance or mixture

Combustion products or resulting gases: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), metal oxides.

#### · 5.3 Advice for firefighters

- **Protective equipment:** Use breathing apparatus.

### 6 Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

#### · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Pick up mechanically.

(Contd. on page 4)



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 3)

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

**7.1 Precautions for safe handling**

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:** No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep container tightly sealed.

Keep container dry, in a waterproof place.

**7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****14808-60-7 Quartz (SiO<sub>2</sub>)**TLV | Long-term value: 0,1 mg/m<sup>3</sup>  
respirable fraction**65997-15-1 Cement, portland, chemicals**TLV | TWA 10 mg/m<sup>3</sup> (total dust)**Cement, White Cement , EN 197-1 CEM 1**TLV | TWA 10 mg/m<sup>3</sup> (total inhalable dust)  
TWA 4 mg/m<sup>3</sup> (Respirable dust)**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure adequate ventilation.

**Respiratory protection:** Not required.

(Contd. on page 5)



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 4)

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

Form:	Powder
Colour:	Grey
· Odour:	Odourless
· Odour threshold:	Not determined.

· pH-value: Not applicable.

**· Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	2230 °C

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

**· Ignition temperature:**

Decomposition temperature: Not determined.

(Contd. on page 6)



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 5)

· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b> <b>Lower:</b> <b>Upper:</b>	Not determined. Not determined.
· <b>Vapour pressure:</b>	Not applicable.
· <b>Density:</b> · <b>Relative density</b> · <b>Vapour density</b> · <b>Evaporation rate</b>	Not determined. Not determined. Not applicable. Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Negligible
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not applicable. Not applicable.
· <b>Solvent content:</b> <b>Organic solvents:</b> <b>VOC (EC)</b>	0,0 % 0.00 %
<b>Solids content:</b>	100,0 %
· <b>9.2 Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** The product is stable under normal terms of use.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide, Carbon dioxide, Metal oxides.

### 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.

(Contd. on page 7)

IL



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

**Trade name: Sika Rep Power**

(Contd. of page 6)

- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**  
May cause cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### 12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)



## Safety data sheet

According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

Trade name: Sika Rep Power

(Contd. of page 7)

### 14 Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

### 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms GHS05, GHS07, GHS08
- Signal word Danger
- Hazard-determining components of labelling:  
Cement, portland, chemicals  
Blended Portland Cement
- Hazard statements  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H350 May cause cancer.  
H335 May cause respiratory irritation.
- Precautionary statements  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 9)





## Safety data sheet

### According to 1907/2006\ EEC

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

**Trade name: Sika Rep Power**

(Contd. of page 8)

P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. All information contained in the present sheet is based on the manufacturer data. The use of this product is not subject to our direct control: therefore, users must under their own responsibility comply with the current health and safety laws and regulation.

### · Relevant phrases

H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.

· **Department issuing SDS:** Product safety department.

### · Contact:

Gilar LTD - Sika Israel  
Hamatechet st. 6, 60920 Qadima, Israel  
Phone: +972 989 94006 Mobile: +972 544 527 212 Fax: +972 989 94016

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 10)



**Safety data sheet**  
**According to 1907/2006\ EEC**

Printing date 11.12.2016

Version number 1

Revision: 11.12.2016

**Trade name: Sika Rep Power**

(Contd. of page 9)

Carc. 1A: Carcinogenicity – Category 1A

Carc. 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

. \* **Data compared to the previous version altered.**

IL