According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Date of last issue: -Revision Date: SDS Number:

00.00.0000 0.0 000000023916 Date of first issue: 13.07.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor 156 B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product is not intended for consumer use, Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Yapi Kimyasallari A.S.

İstanbul Deri Organize Sanayi Bölgesi 2. yol

J-7 Parsel / Aydınlı Orhanlı Mevkii

34944 Tuzla / İstanbul

Turkey

+90 216 581 06 00 Telephone Telefax +90 216 581 06 99 +90 216 581 06 00 / 1260

Emergency telephone num-

E-mail address of person

responsible for the SDS

: EHS@tr.sika.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification T.R. SEA No 28848

H302: Harmful if swallowed. Acute toxicity, Category 4

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin corrosion, Category 1B H314: Causes severe skin burns and eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling T.R. SEA No 28848

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

Hazard pictograms





Signal word : Danger

Hazard statements : H302 + H332 Harmful if swallowed or if inhaled

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with wa-

ter for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P310 Immediately call a POISON

CENTER/doctor.

Hazardous components which must be listed on the label:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

3,6,9-triazaundecamethylenediamine

2,4,6-tris(dimethylaminomethyl)phenol

3-[(6-aminotrimethylhexyl)amino]propiononitrile

trimethylhexane-1,6-diamine

2.3 Other hazards

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No.	T.R. SEA No 28848	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 25 - < 50
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Chronic3; H412 Eye Dam.1; H318	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0 216-032-5	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 10 - < 20
3,6,9- triazaundecamethylenediamine	112-57-2 203-986-2	1; H318 Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phen ol <= 15 %	90-72-2 202-013-9	Skin Sens.1B; H317 1C; H314 Aquatic Chronic3; H412 Acute Tox.4; H302 1; H319	>= 5 - < 10
3-[(6- aminotrimethylhex- yl)amino]propiononitrile	93941-62-9 300-511-1	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 2,5 - < 5
trimethylhexane-1,6-diamine	25620-58-0 247-134-8	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 1 - < 2,5

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Respiratory disorder Allergic reactions

Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects sensitising effects

Harmful if swallowed or if inhaled May cause an allergic skin reaction.

Causes serious eye damage.

Causes severe burns.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Date of last issue: -Revision Date: SDS Number:

00.00.0000 000000023916 Date of first issue: 13.07.2016 0.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : amine-like

Odour Threshold : No data available

Flash point : > 101 °C

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

Autoignition temperature : ca. 420 °C

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Oxidizing properties : No data available

pH : > 11

Melting point/range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Vapour pressure : 19,9983 hPa

Density : ca.1,018 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : ca.12 mPa.s

at 20 °C

Viscosity, kinematic : > 7 - < 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled

Components: benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1.030 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1.716,2 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1.260 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

Remarks: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: No data available

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Product:

Remarks: May cause an allergic skin reaction.

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Assessment: The product is a skin sensitiser, sub-category 1A. Result: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Product:

Germ cell mutagenicity- As- : No data available

sessment

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assess-

: No data available

ment

Reproductive toxicity

Not classified based on available information.

Product:

Reproductive toxicity - As-

: No data available

sessment

Teratogenicity - Assessment : No data available

STOT - single exposure

Not classified based on available information.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10

- 100 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

 ADR
 : UN 1760

 IMDG
 : UN 1760

 IATA
 : UN 1760

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, N.O.S.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

IMDG : CORROSIVE LIQUID, N.O.S.

IATA : Corrosive liquid, n.o.s.

14.3 Transport hazard class(es)

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : III Labels : 8

EmS Code : F-A, S-B

IATA

Packing instruction (cargo : 856

aircraft)

Packing instruction (passen-

ger aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosives

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: 852

Not applicable for product as supplied.

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Date of last issue: -Version Revision Date: SDS Number:

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: Not applicable

: Not applicable

: Not applicable

(=> 0.1 %).

: Not applicable

: Not applicable

: Not applicable

: Not applicable

: None of the components are listed

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Ministry of Environment and Forestry; Regulation on Restriction Regarding to Manufacture, Placing on the Market and Use of Certain Hazardous Substances, Preparations and Articles. Dated 26 December 2008. Numbered 27092 (Bis).

major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Remarks: no VOC duties

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

Directive 1999/13/EC

Volatile organic compounds (VOC) content: 48 %, 488,64 g/l

Remarks: VOC content excluding water

Directive 1999/13/EC

Volatile organic compounds (VOC) content: 48 %, 488,64 g/l Remarks: VOC content valid only for coating materials used

on wood surfaces

14 / 16

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Half maximal effective concentration
IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



Sikafloor 156 B

Version Revision Date: SDS Number: Date of last issue: -

0.0 00.00.0000 000000023916 Date of first issue: 13.07.2016

SDS Author

Atilim Yetiskin yetiskin.atilim@tr.sika.com +902165810647

Certification Number: 01.44.09 Certification Date: 15.04.2015

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

TR / EN