

SAFETY DATA SHEET

Sikafloor 155 W Part B

Date of issue - 08/04/2013. SKFL15WB

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code SKFL15WB

Product Name Sikafloor 155 W Part B

Product Description 2-component water dispersible epoxy resin based primer.

Manufacturer/Supplier Sika Limited

Watchmead

Welwyn Garden City Hertfordshire. AL7 1BQ

tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Preparation - Hazardous ingredients (Europe)

Classification Component **CAS/EINECS** Concentration **Risk Phrases** R21/22, R34, R43, Isophoronediamine 2855-13-2 1.00% - 2.50% C R52/53 R20/22, R34, R43. С M-phenylebis(methylamine) 1477-55-0 1.00% - 2.50% R52/53

3. HAZARD IDENTIFICATION

Main Hazards May cause sensitization by skin contact.

Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

4. FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15

minutes, holding the eye open. Obtain medical attention urgently.

Skin Contact Wipe off as much as possible with a clean dry cloth. Wash skin

thoroughly with soap and water.

Solvents should not be used to clean skin because they may

increase the penetration of the material.

Ingestion Do not induce vomiting. Wash out mouth with water.

Obtain medical attention.

Inhalation Remove from exposure.

Seek medical attention if you feel unwell.

5. FIRE FIGHTING MEASURES

Extinguishing Media Not readily combustible.

Use foam, dry chemical or carbon dioxide.

Extinguishing Media - Not suitable Do not use water jet.

Special Hazards of Product Combustion will generate oxides of carbon and nitrogen

Protective Equipment for Fire-Fighting Wear full protective clothing and self-contained breathing

apparatus.

CM Version - 3 Page: 1/4



SAFETY DATA SHEET

Sikafloor 155 W Part B

Date of issue - 08/04/2013. SKFL15WB

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear appropriate protective clothing.

Environmental Precautions and Clean-up

Try to prevent the material from entering drains or water courses.

Methods **Spillages**

Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Handling

Use in well ventilated area.

Storage

Avoid contact with eyes, skin and clothing. Storage area should be: cool. dry.

Protect from extremes of cold.

Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed. Keep away from

foodstuffs

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Control Measures

Use of the basic principles of Industrial Hygiene will enable this

material to be used safely.

Respiratory Protection

Respiratory protection not normally required.

Hand Protection

Eye Protection

Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean. Wear safety glasses if risks of accidental contamination are

possible during application.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid. Color Colorless. **Odor** Amine like. Flash Point °C Not applicable.

Solubility - Water Miscible.

Density (kg/m3) Approx. 1000 at 20 °C.

Viscosity (at 20 °C) Mobile liquid at ambient temperatures.

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Conditions to avoid Extremes of temperature.

Protect from frost

Hazardous Decomposition Products Heating may produce: oxides of carbon. acrid smoke and irritating

fumes.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Low order of acute toxicity.

Eve irritation May cause slight transient irritation.

Skin irritation Frequent or prolonged skin contact may cause some local short

term skin irritation.

Sensitization - Skin The possibility of allergic sensitisation should be considered

CM Version - 3 Page: 2/4



SAFETY DATA SHEET Sikafloor 155 W Part B

Date of issue - 08/04/2003. SKFL15WB

12. ECOLOGICAL INFORMATION

Mobility Emulsifiable in water.

Persistence/degradability

The product is expected to be not readily biodegradable.

EcotoxicityThis material is harmful to aquatic organisms.

13. DISPOSAL

Product Disposal Dispose of as Special Waste.

Arrange for disposal via a licensed waste contractor.

Container Disposal Dispose of containers with care.

Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste

contractor.

14. TRANSPORT INFORMATION

ADR/RID : Proper shipping nameNot Regulated under ADR/RIDIMDG : Proper shipping nameNot Regulated under IMDGIATA : Proper shipping nameNot Regulated under ICAO

15. REGULATORY INFORMATION

Label Requirements Irritant, Dangerous for the environment

K

*

Risk PhrasesMay cause sensitization by skin contact.

Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Safety Phrases Avoid contact with skin.

Wear suitable gloves.

Contains epoxy constituents. See information supplied by the

manufacturer.

Contains M-phenylebis(methylamine)

3-aminomethyl-3,5,5 trimethylcyclohexylamine

16. OTHER INFORMATION

First Issue Date 08.07.1998
Revisions Highlighted Main Hazards

Physical and Chemical Properties

Regulatory Information

Uses and Restrictions Customer's are urged to ensure that the product is entirely suitable

for their own purpose. It is the customer's responsibilty to ensure that a suitable and sufficient assessment of the risks created by

the use of the product is undertaken.

CM Version - 3 Page: 3/4



SAFETY DATA SHEET Sikafloor 155 W Part B

Date of issue - 08/04/2003.

SKFL15WB

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory

Provisions.

Chemicals (Hazard Information and Packaging) Regulations, 2002. SI 1999/437: The Control of Substances Hazardous to Health

Regulations

SI No. 972/1996: The Special Waste Regulations 1996 SI No 2839 1991 Environmental Protection (Duty of Care)

Regulations.

UK Guidance Publications

General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication.All warranties are

excluded. Our most current General Sales Conditions shall apply.

Please consult the Technical Data Sheet prior to use.