

Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

Date of printing: 03.05.2013

Page: 1/6

Revised:

SDS No.: -00022338.0000

1. Identification of the substance/preparation and company

Product

Product name

SIKADUR 281 (Sikadur 42 comp A)

Manufacturer/supplier information

Manufacturer/supplier:

Sika S.A.

Street/postbox:

Carretera de Fuencarral, 72 Pol Ind

Town/City and Post Code:

28108 Alcobendas (Madrid)

Country:

España

Phone:

91 662 18 18

Telefax:

91 662 19 38

General information:

Emergency information phone:

91 662 18 18

Durante el horario normal de trabajo

2. Composition/information on ingredients

Hazardous ingredients

Designation according to 67/548/EEC

CAS No. Concentration Danger symbols R phrases

EC No.

- reaction product: bisphenol A-(epichlorhydrin)
epoxy resin (number average molecular weight \leq 700)
25068-38-6 50 - 100 % Xi,N 36/38,43,51/53
500-033-5
- Oxirane, mono[(C10-16-alkyloxy)methyl] derivatives
68081-84-5 2.5 - 10 % Xi,N 36/38,51/53,43
268-358-2
- Solvent naphtha (petroleum), heavy arom., bp > 240°C
64742-94-5 2.5 - 10 % Xn,N 65,51/53,66,67
265-198-5

3. Hazards identification

Hazards identification

Xi

Irritant

N

Dangerous for the environment

Information on hazards to man and to the environment

36/38

Irritating to eyes and skin.

43

May cause sensitization by skin contact.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First-aid measures

General instructions

In any case show the physician the Safety Data Sheet

After inhalation

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Summon a doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

compatible with all usual extinguishing media

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO₂)

Nitrogen oxides (NO_x)

Additional information

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Product name: **SIKADUR 281**

Date of printing: 03.05.2013

Page: 3/6

Revised:

SDS No.: -00022338.0000

6. Accidental release measures (continued)

When picked up, treat material as prescribed under heading "Disposal".

7. Handling and storage

Handling

Instructions for safe handling

See chapter 8 / Personal protective equipment.

Instructions for fire and explosion protection

Not applicable.

Storage

Requirements for storage rooms and containers

Keep container tightly closed and dry in a cool, well-ventilated place

Combined storage instructions

Keep away from food, beverages and animal feedstocks.

Additional information regarding storage

Protect from frost.

Protect from heat and direct sunlight

Protect from atmospheric moisture and water

8. Exposure controls/personal protection

Personal protective equipment

General protective and hygiene measures

Take care for sufficient ventilation or exhaust on the workshop place.

Avoid contact with eyes and skin

Use barrier skin cream.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

Respiratory protection

Not applicable.

Hand protection

Butyl rubber/nitrile rubber gloves

Eye protection

Tightly fitting safety glasses

Body protection

Working clothes

Product name: **SIKADUR 281**

Date of printing: 03.05.2013

Page: 4/6

Revised:

SDS No.: -00022338.0000

9. Physical and chemical properties

Appearance

Physical state: liquid

Data relevant to safety

Method

1.14 g/cm³

Viscosity at 20°C

1400 mPas

VOC (solvents)

6.58 %

VOC (CH)

0.05 %

10. Stability and reactivity

Materials to avoid/dangerous reactions

No hazardous reactions when stored and handled according to prescribed instructions.

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

11. Toxicological information

Sensitization

Sensitization/allergic reaction possible.

Allergic reaction may be observed in sensitive persons, even on very low concentrations.

Experience on humans

When skin contact:

Irritation.

When eyes contact:

Irritation.

When inhalation:

Irritation.

When swallowed:

Small amount may cause considerable health disorders.

12. Ecological information

Additional information

Do not allow to enter waste water drain, waterways or soil.

13. Disposal considerations

Product

Recommendations

Must be disposed of in a special waste disposal unit in accordance with the corresponding regulations.

Product name: **SIKADUR 281**

Date of printing: 03.05.2013

Page: 5/6

Revised:

SDS No.: -00022338.0000

13. Disposal considerations (continued)

See chapter 15, national regulations.

Packaging

Recommendations

Completely emptied packagings may be given for recycling.

Empty packaging may still contain hazardous residues.

Empty packaging should be removed by a licensed waste contractor.

14. Transport information

IMO/IMDG

EmS: 999

Marine pollutant: no

15. Regulatory information

Labelling according to EEC Directive

The product is classified and labelled in accordance with

EC directives/the relevant national laws.

Relevant hazardous ingredients for labelling

Contains: reaction product: bisphenol A-(epichlorhydrin)

epoxy resin (number average molecular weight <= 700)

Oxirane, mono[(C10-16-alkyloxy)methyl] derivatives

Danger symbols

Xi Irritant

N Dangerous for the environment

R phrases

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases

2 Keep out of the reach of children.

24 Avoid contact with skin.

29 Do not empty into drains.

37 Wear suitable gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

Special labelling for certain preparations

Contains epoxy constituents. See information supplied by the manufacturer.

Product name: **SIKADUR 281**

Date of printing: 03.05.2013

Page: 6/6

Revised:

SDS No.: -00022338.0000

16. Other information

asterisk (*) on left margin marks modification of previous version

Recommended use: Chemical product for construction and industry

R-phrases of the ingredients listed in chapter 2

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.