



GREENSTREAK GROUP, INC

Introducing WB Primer Adhesive A New Water Based Primer Adhesive For **SWELLSTOP™**



A water based primer is now available for Swellstop, Greenstreak's clay based, controlled expansion hydrophilic waterstop. There are several benefits to choosing a water based alternative, including:

- Improved / Extended coverage, approximately 2,400 linear feet per gallon
- Reduced dry time
- Cleans with soap and water while still wet
- Non-hazmat shipping
- Low VOC content / VOC compliant



Application Instructions

It is essential that the instructions below be followed carefully.

WB Primer Adhesive

1. Apply only to cured, dry concrete surfaces.
2. Prepare application area by removing all loose particles and dirt.
3. Apply by brushing a strip of primer adhesive wide enough to cover the Swellstop material once it's applied - usually two (2) inches wide.
4. Allow to dry for 15-30 minutes depending on temperature and humidity.

Swellstop Waterstop

1. Press Swellstop firmly onto primed surface. Achieve a spread of about 25% of the material width.
2. Butt coil ends together and never overlap. Press ends together until there is no separation and no air pockets.
3. Surface area is now ready to receive a second concrete placement.

COVERAGE: Approximately 2,400 linear feet per gallon.

STORAGE: After container has been initially opened, maintain a tight seal at room temperature.

Do Not Freeze.

CLEAN-UP: Application tools and equipment can be cleaned with soap and water while wet or mineral spirits when dry.

GREENSTREAK GROUP, INC.
800-325-9504 www.Greenstreak.com


Greenstreak Group, Inc. 
is a subsidiary of Sika Corporation