

# Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH  
Regulation, 453/2010/EC and Regulation No 1272/2008/EC  
(CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** SIKALASTIC 110S
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No relevant identified uses-mixture of substances.
- **Application of the substance / the mixture** Polyurethane Waterproofing Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GILAT LTD  
3 Haaruv St.  
Modi'in industrial park  
Israel +972 9 8994000
- **1.4 Emergency telephone number:**  
Emergency telephone number: +972  
9 8994004

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation EC No 1272/2008 CLP**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 1)

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R20-48/20/21/22: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.



Xi; Irritant

R36/38: Irritating to eyes and skin.



Xn; Sensitising

R42: May cause sensitisation by inhalation.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the Classification Directive for preparations of the EU in the latest valid version.

· **Classification system:**

The classification of the product is according CLP Regulation 1272/2008/EC and European Directive 99/45/EC.

· **2.2 Label elements**· **Labelling according to Regulation EC No 1272/2008 CLP**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labelling:**

xylene, mixture of isomers  
m-tolylidene diisocyanate  
ethylbenzene  
4,5-dichloro-2-octyl-2H-isothiazol-3-one

· **Hazard statements**

H226 Flammable liquid and vapour.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 3)

GB

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 2)

· **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P331 Do NOT induce vomiting.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.






· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene, mixture of isomers  Xn R20/21-48/20/21/22-65;  Xi R36/37/38  Flam. Liq. 3, H226;  STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<20%
---	--	---------

(Contd. on page 4)

# Safety Data Sheet



























## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene  Xn R20;  F R11  Flam. Liq. 2, H225;  Acute Tox. 4, H332	(Contd. of page 3) 3-<10%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-300-00-2	Naphtha (petroleum), hydrodesulfurized heavy  Xn R65;  N R51/53 R67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H336	0.1-<0.3%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolylidene diisocyanate  T+ R26;  Xn R40;  Xn R42/43;  Xi R36/37/38 R52/53 Carc. Cat. 3  Acute Tox. 2, H330;  Resp. Sens. 1, H334; Carc. 2, H351;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	0.1-<1%
CAS: 64359-81-5 EINECS: 264-843-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one  T+ R26;  C R35;  Xn R22;  Xi R43;  N R50  Acute Tox. 1, H330;  Met. Corr. 1, H290; Skin Corr. 1A, H314;  Aquatic Acute 1, H400;  Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-<0.3%

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice.

##### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Seek medical treatment in case of complaints.

(Contd. on page 5)

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 4)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Do not induce vomiting; call for medical help immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.  
Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Self contained breathing apparatus and full protective clothing must be worn in case of fire.
- **Additional information**  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable receptacles.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 6)

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· **Trade name: SIKALASTIC 110S**

See Section 13 for disposal information.

(Contd. of page 5)

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

#### · Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Keep respiratory protective device available.

Keep it in a dry, cool, well ventilated, fixed in advance place, away from sources of heat, flames, ignition and direct sunlight.

#### · 7.2 Conditions for safe storage, including any incompatibilities

##### · Storage:

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Store away from foodstuffs.

##### · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store under lock and key and with access restricted to technical experts or their assistants only.

Store under lock and key and out of the reach of children.

#### · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

##### · Ingredients with limit values that require monitoring at the workplace:

##### 1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

##### 100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

(Contd. on page 7)

# Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH  
Regulation, 453/2010/EC and Regulation No 1272/2008/EC  
(CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 6)

**26471-62-5 m-tolylidene diisocyanate**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

· **Ingredients with biological limit values:****1330-20-7 xylene, mixture of isomers**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

GB

# Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH  
Regulation, 453/2010/EC and Regulation No 1272/2008/EC  
(CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 7)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

PVC gloves

· **Eye protection:**

Tightly sealed goggles

· **Body protection:**

Protective work clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Viscous

Colour: Black

· **Odour:** Characteristic

· **Odour threshold:** Not determined

· **pH value:** Not determined

· **Melting point/Melting range:** Not determined

· **Boiling point/Boiling range:** Not determined

· **Flash point:** Not determined

· **Flammability (solid, gaseous):** Not applicable

· **Autoignition temperature:** Not determined

· **Decomposition temperature:** Not determined

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: Not determined

(Contd. on page 9)



# Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH  
Regulation, 453/2010/EC and Regulation No 1272/2008/EC  
(CLP)

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 8)

<b>Upper:</b>	Not determined
· <b>Vapour pressure:</b>	Not determined
· <b>Density:</b>	Not determined
· <b>Relative density</b>	Not determined
· <b>Vapour density</b>	Not determined
· <b>Evaporation rate</b>	Not determined
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined
<b>Kinematic at 20 °C:</b>	90 s (ISO 2431: 1993 ; 6mm JET)
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	170 g/l
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Stable at environment temperature.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

### ATE (Acute Toxicity Estimates)

Dermal	LD50	6322 mg/kg
Inhalative	LC50/4 h (vapour)	18.5 mg/l

### 100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

(Contd. on page 10)

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 9)

Inhalative	LC50-4h	4000 ppm (rat)
<b>26471-62-5 m-tolylidene diisocyanate</b>		
Oral	LD50	4130 mg/kg (rat)
Dermal	LD50	>9400 mg/kg (rabbit)
Inhalative	LC50/4 h (vapour)	0.107 mg/l (rat)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitisation:** Sensitisation possible through inhalation.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Carcinogenic.

The product can cause inheritable damage.

- **Sensitisation** Sensitization possible through skin contact

### SECTION 12: Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:**

<b>26471-62-5 m-tolylidene diisocyanate</b>	
EC50-48h	12.5 mg/l (daphnia magna)
LC50-96h	133 mg/l (Con)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 11)

# Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH  
Regulation, 453/2010/EC and Regulation No 1272/2008/EC  
(CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 10)

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

### · Uncleaned packaging:

#### · Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

## SECTION 14: Transport information

### · 14.1 UN-Number

· ADR, ADN, IMDG

Void

· IATA

UN1866

### · 14.2 UN proper shipping name

· ADR, ADN, IMDG

Void

· IATA

RESIN SOLUTION

### · 14.3 Transport hazard class(es)

· ADR, ADN, IMDG

· Class

Void

· IATA



· Class

3 Flammable liquids.

· Label

3

### · 14.4 Packing group

· ADR, IMDG

Void

· IATA

III

### · 14.5 Environmental hazards:

Not applicable.

(Contd. on page 12)

GB

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP)

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 11)

· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Remarks:</b>	No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG ADR: Containers >450 l = UN 1866 - 3(F1) - RESIN SOLUTION, flammable IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
· <b>IMDG</b> · <b>Remarks:</b>	No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG ADR: Containers >450 l = UN 1866 - 3(F1) - RESIN SOLUTION, flammable IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
· <b>UN "Model Regulation":</b>	-

### SECTION 15: Regulatory information

#### · **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

The mixture classification is according to CLP Regulation 1272/2008/EC and European Directive 99/45/EC.

#### · **Labelling according to Regulation (EC) No 1272/2008** Label elements in Section 2.2

#### · **National regulations:**

#### · **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 13)

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP))

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· Trade name: SIKALASTIC 110S

(Contd. of page 12)

## · Other regulations, limitations and prohibitive regulations

## · Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

## · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R26	Very toxic by inhalation.
R35	Causes severe burns.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

(Contd. on page 14)

GB

# Safety Data Sheet

## complying with Regulation 1907/2006/EC (REACH Regulation, 453/2010/EC and Regulation No 1272/2008/EC (CLP)

Printing date 11.12.2018

Version number 2

Revision: 10.12.2018

· **Trade name: SIKALASTIC 110S**

(Contd. of page 13)

- R50 Very toxic to aquatic organisms.  
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R65 Harmful: may cause lung damage if swallowed.  
 R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

SUSTCHEM Engineering Ltd  
 REACH & Chemical Services Department  
 144, 3rd Septemvriou, GR 112 51, Athens, Greece  
 Tel.: +30 210 8252510-4 Fax: +30 210 8252575  
 E-mail: [info@suschem.gr](mailto:info@suschem.gr)  
 Website: [www.sustchem.gr](http://www.sustchem.gr)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Met. Corr. 1: Corrosive to metals, Hazard Category 1  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Acute Tox. 1: Acute toxicity, Hazard Category 1  
 Acute Tox. 2: Acute toxicity, Hazard Category 2  
 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1  
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
 Carc. 2: Carcinogenicity, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **\* Data compared to the previous version altered.**

Classification and labelling according to CLP regulation.