

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika MonoTop®-3130 Ultra Rapid

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier Gilar LTD - Sika Israel
3 Haruv st. Modii'n Industrial
park, Shoham, Israel 7319900
Telephone +972 3 9019004
E-mail address of person
responsible for the SDS info@gilar.co.il

1.4 Emergency telephone number

+972 3 9019004

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022

Version 1.0

Print Date 29.04.2022

Date of last issue: -

| | | |
|--------------------------|---------------------------|--|
| | H335 | May cause respiratory irritation. |
| Precautionary statements | P101 | If medical advice is needed, have product container or label at hand. |
| | P102 | Keep out of reach of children. |
| | Prevention: | |
| | P271 | Use only outdoors or in a well-ventilated area. |
| | P280 | Wear protective gloves/ eye protection/ face protection. |
| | Response: | |
| | P305 + P351 + P338 + P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. |
| | Disposal: | |
| | P501 | Dispose of contents/container in accordance with local regulation. |

Hazardous components which must be listed on the label:

Cement, portland, chemicals

2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006.

The product reacts highly alkaline with water.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| Cement, portland, chemicals | 65997-15-1 266-043-4 | Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 | >= 10 - < 20 |
| Cement (chromium reduced) | 65997-15-1 266-043-4 | Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) | >= 10 - < 20 |
| calcium oxide | 1305-78-8 215-138-9 01-2119475325-36-XXXX | Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 | >= 1 - < 2,5 |
| calcium dihydroxide | 1305-62-0 215-137-3 01-2119475151-45-XXXX | Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) | >= 1 - < 2,5 |
| Substances with a workplace exposure limit : | | | |
| Quartz (SiO ₂) | 14808-60-7 238-878-4 | | >= 40 - < 60 |
| Quartz (SiO ₂) | 14808-60-7 238-878-4 | | >= 10 - < 20 |
| calcium sulfate | 7778-18-9 231-900-3 01-2119444918-26-XXXX | | >= 5 - < 10 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
 Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
 Wash off with soap and plenty of water.
 If symptoms persist, call a physician.



- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
-



for firefighters

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated



areas and containers : place. Store in accordance with local regulations.

Further information on storage stability : Keep in a dry place.
 No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|----------------------------|---|-------------------------------|-----------------------|---------|
| Quartz (SiO ₂) | 14808-60-7 | NGV (Respirable fraction) | 0,1 mg/m ³ | SE AFS |
| | Further information: Inhalable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method., Substance is carcinogenic., Medical control may be required for the handling of the substance. See further regulations on medical control in the workplace. For some substances the employer must provide medical examination and for other substances apply periodic medical examinations and employability assessments. See the regulations on chemical working environment risks and regulations on quartz - stone dust in the working environment. | | | |
| Quartz (SiO ₂) | 14808-60-7 | NGV (Respirable fraction) | 0,1 mg/m ³ | SE AFS |
| | Further information: Inhalable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and | | | |

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
 Date of last issue: -

Version 1.0

Print Date 29.04.2022

| | | | | |
|-----------------|---|----------------------------|-----------|-------------|
| | <p>having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method., Substance is carcinogenic., Medical control may be required for the handling of the substance. See further regulations on medical control in the workplace. For some substances the employer must provide medical examination and for other substances apply periodic medical examinations and employability assessments. See the regulations on chemical working environment risks and regulations on quartz - stone dust in the working environment.</p> | | | |
| calcium sulfate | 7778-18-9 | NGV (Respirable fraction) | 2,5 mg/m3 | SE AFS |
| | <p>Further information: Inhalable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method., For dust or mist of substances with special limit values, those values apply.</p> | | | |
| | | NGV (inhalable fraction) | 5 mg/m3 | SE AFS |
| calcium oxide | 1305-78-8 | TWA (Respirable fraction) | 1 mg/m3 | 2017/164/EU |
| | Further information: Indicative | | | |
| | | STEL (Respirable fraction) | 4 mg/m3 | 2017/164/EU |
| | | NGV (inhalable fraction) | 1 mg/m3 | SE AFS |
| | <p>Further information: Inhalable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total</p> | | | |

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
 Date of last issue: -

Version 1.0

Print Date 29.04.2022

| | | | | |
|---|-----------|--|---------|-------------|
| | | dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method. | | |
| | | KGV (inhalable fraction) | 4 mg/m3 | SE AFS |
| calcium dihydroxide | 1305-62-0 | TWA (Respirable fraction) | 1 mg/m3 | 2017/164/EU |
| Further information: Indicative | | | | |
| | | STEL (Respirable fraction) | 4 mg/m3 | 2017/164/EU |
| | | NGV (inhalable fraction) | 1 mg/m3 | SE AFS |
| Further information: Inhalable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable fraction refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method. | | | | |
| | | KGV (inhalable fraction) | 4 mg/m3 | SE AFS |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
 Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
 Eye wash bottle with pure water

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

 Recommended: Butyl rubber/nitrile rubber gloves.
 Contaminated gloves should be removed.

- Skin and body protection : Dust impervious protective suit
 Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
particulate filter P
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid
Appearance : powder
Colour : grey

Odour : slight

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : Not applicable

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : > 11
Concentration: 50 %

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-
octanol/water : No data available

Vapour pressure : No data available

Density : No data available

Bulk density : ca. 1,4 kg/m³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product** : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue** : 16 03 03* inorganic wastes containing dangerous substances
: 17 01 01 concrete
- Contaminated packaging** : 15 01 10* packaging containing residues of or contaminated by dangerous substances
- Remarks** : Product is hazardous waste if the EWC-code is marked with *.

SECTION 14: Transport information

14.1 UN number

- ADR** : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

- ADR** : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

- ADR** : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

- ADR** : Not regulated as a dangerous good

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022
Date of last issue: -

Version 1.0

Print Date 29.04.2022

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people who will be turning 16 during the calendar year are, however, except from this rule if the product is a necessary part of their education.

AFS 2011:19 - Chemical Hazards in the Working Environment (amended by AFS 2019:9), §§37a-g.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
SE AFS : Sweden. Occupational Exposure Limit Values
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
SE AFS / NGV : Time Weighted Average
SE AFS / KGV : Short Term Exposure Limit
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika MonoTop®-3130 Ultra Rapid



Revision Date: 21.04.2022

Version 1.0

Print Date 29.04.2022

Date of last issue: -

| | |
|--------|--|
| | air that kills 50% of the test animals during the observation period) |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : Occupational Exposure Limit |
| PBT | : Persistent, bioaccumulative and toxic |
| PNEC | : Predicted no effect concentration |
| REACH | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : Substances of Very High Concern |
| vPvB | : Very persistent and very bioaccumulative |

Further information

Classification of the mixture:

| | |
|---------------|------|
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H335 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

IL / EN